APC BV650I-GR gruppo di continuità (UPS) A linea interattiva 0,65 kVA 375 W 4 presa(e) AC



Marchio : APC

Codice prodotto: BV650I-GR

Nome del prodotto : BV650I-GR

APC BV650I-GR. Topologia UPS: A linea interattiva, Potenza in uscita: 0,65 kVA, Potenza in uscita: 375 W. Tipo di uscita AC: Tipo F, Quantità prese AC: 4 presa(e) AC. Tecnologia batteria: Acido piombo (VRLA), Capacità della batteria: 7 Ah, Voltaggio della batteria: 12 V. Fattore di forma: Compatta, Colore del prodotto: Nero, Lunghezza cavo: 1,52 m. Certificati di conformità: RoHS, Certificazione: CE REACH



Caratteristiche	
Topologia UPS *	A linea interattiva
Potenza in uscita *	0,65 kVA
Potenza in uscita *	375 W
Forma d'onda *	Sinusoidale
Tensione operativa in entrata (min) *	170 V
Tensione operativa in entrata (max) *	280 V
Frequenza di ingresso *	50/60 Hz
frequenza output	50/60 Hz
Regolatore automatico di tensione (AVR)	✔
Valutazione sovraccarico energetico	156 J
Tempo di trasferimento (dalla modalità di linea alla modalità batteria)	6 ms
Numero di fasi di ingresso	1
Numero di fasi di uscita	1
Emissione acustica	40 dB
Protezione contro le sovratensioni	✔
Allarmi sonori	✔
Modalità allarme acustici	Allarme in funzionamento a batteria, Allarme per batteria scarsa, Allarme di sovraccarico

Connettività	
Tipo di uscita AC	Tipo F
Quantità prese AC	4 presa(e) AC
SmartSlot	✘
Porta SmartConnect	✘

Batteria	
Tecnologia batteria	Acido piombo (VRLA)
Capacità della batteria	7 Ah
Voltaggio della batteria	12 V

Batteria	
Tempo di ricarica	8 h
Partenza a freddo	✔

Design	
Fattore di forma *	Compatta
Lunghezza cavo	1,52 m
Colore del prodotto *	Nero
Indicatori LED	✔

Condizioni ambientali	
Intervallo temperatura di funzionamento	0 - 40 °C
Range di umidità di funzionamento	0 - 90%
Altitudine di funzionamento	0 - 1968,3 m

Certificati di sicurezza	
Certificati di conformità	RoHS
Certificazione	CE REACH

Contenuto dell'imballo	
Scheda di gestione inclusa	✘

Dimensioni e peso	
Larghezza	160 mm
Profondità	305 mm
Altezza	92 mm
Peso	4,5 kg

Dati su imballaggio	
Larghezza imballo	373 mm
Profondità imballo	143 mm
Altezza imballo	237 mm
Peso dell'imballo	4,8 kg

Dati logistici	
Codice del Sistema Armonizzato (SA)	85078000

Altre caratteristiche	
Voltaggio di output nominale	230 V



0731304338321



731304338321

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 02-NOV-2026. Prints or copies of Information are only valid on the printed Publication date