D-Link DMS-108P/E switch di rete Non gestito 2.5G Ethernet (100/1000/2500) Supporto Power over Ethernet (PoE) Nero





Marchio : D-Link

Codice prodotto: DMS-108P/E

Nome del prodotto : DMS-108P/E

D-Link DMS-108P/E. Tipo interruttore: Non gestito. Tipo di porte RJ-45: 2.5G Ethernet (100/1000/2500), Quantità di porte RJ-45: 8. Dimensioni tavola MAC: 4000 voci, Capacità di commutazione: 40 Gbit/s. Standard di rete: IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3bz, IEEE 802.3u,.... Voltaggio input DC: 54 V. Connettore di alimentazione: Jack DC-ingresso. Supporto Power over Ethernet (PoE)

Caratteristiche di gestione	
Tipo interruttore *	Non gestito
Supporto qualità del servizio (QoS)	✔
Classificazione del traffico	✔

Connettività	
Quantità di porte RJ-45 *	8
Tipo di porte RJ-45 *	2.5G Ethernet (100/1000/2500)
Connettore di alimentazione	Jack DC-ingresso

Collegamento in rete	
Standard di rete *	IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3bz, IEEE 802.3u, IEEE 802.3x
Supporto 10G *	✘
Auto MDI/MDI-X	✔
Velocità trasferimento Ethernet LAN	10,100,1000,2500 Mbit/s

Trasmissione dati	
Capacità di commutazione *	40 Gbit/s
tasso di inoltro	29,76 Mpps
Dimensioni tavola MAC *	4000 voci
Store-and-forward	✔

Design	
Impilabile *	✔
Colore del prodotto	Nero
Indicatori LED	✔

Prestazione	
Tempo medio tra guasti (MTBF)	140688261 h

Gestione energetica	
Alimentazione *	dC

Gestione energetica	
Fonte di alimentazione inclusa *	✔
Voltaggio input DC	54 V
Corrente d'ingresso	4.62 A
Consumo energetico (max)	261,02 W

Power over Ethernet (PoE)	
Supporto Power over Ethernet (PoE) *	✔
Quantità porte Power over Ethernet (PoE)	8
Potenza Power over Ethernet (PoE) per porta	90 W
Bilancio energetico totale del PoE	290 W

Condizioni ambientali	
Intervallo temperatura di funzionamento	0 - 40 °C
Intervallo di temperatura	-10 - 70 °C
Range di umidità di funzionamento	10 - 90%
Umidità	5 - 90%
Dissipazione del calore	890,6 BTU/h

Dimensioni e peso	
Larghezza	190 mm
Profondità	120 mm
Altezza	38 mm
Peso	753 g

Certificati di sicurezza	
Certificazione	CB; UL; LVD; FCC; VCCI; IC; BSMI



0790069476839



790069476839

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 13-NOV-2026. Prints or copies of Information are only valid on the printed Publication date