ZYXEL

Zyxel XGS1935-52HP Gestito L2/L3 Gigabit Ethernet (10/100/1000) Supporto Power over Ethernet (PoE)

Marchio : Zyxel

Codice prodotto: XGS1935-52HP-EU0101F

Nome del prodotto : XGS1935-52HP



Zyxel XGS1935-52HP. Tipo interruttore: Gestito, Livello del commutatore: L2/L3. Tipo di porte RJ-45: Gigabit Ethernet (10/100/1000), Quantità di porte RJ-45: 48. Dimensioni tavola MAC: 16000 voci, Capacità di commutazione: 176 Gbit/s. Standard di rete: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3, IEEE.... Supporto Power over Ethernet (PoE). Montaggio rack



Caratteristiche di gestione	
Tipo interruttore *	Gestito
Livello del commutatore	L2/L3
Supporto qualità del servizio (QoS)	✔

Connettività	
Quantità di porte RJ-45 *	48
Tipo di porte RJ-45 *	Gigabit Ethernet (10/100/1000)
Quantità di slot del modulo SFP+	4

Collegamento in rete	
Standard di rete *	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3ae, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z
Supporto 10G *	✔
VLAN support	✔

Trasmissione dati	
Capacità di commutazione *	176 Gbit/s
tasso di inoltro	130,9 Mpps
Dimensioni tavola MAC *	16000 voci
Supporto Jumbo Frames	✔
Frame Jumbo	9000

Sicurezza	
Caratteristiche DHCP	DHCP Option 82, DHCP client, DHCP relay, DHCPv6 client

Funzioni Multicast	
Supporto multicast	✔

Design	
Montaggio rack *	✔

Gestione energetica	
Alimentazione *	AC
Fonte di alimentazione inclusa *	✔
Tensione di ingresso AC	100 - 240 V
Frequenza di ingresso AC	50/60 Hz
Consumo energetico (max)	470,1 W
Funzionalità di protezione dell'alimentazione	Protezione contro le sovratensioni

Power over Ethernet (PoE)	
Supporto Power over Ethernet (PoE) *	✔
Bilancio energetico totale del PoE	375 W

Condizioni ambientali	
Intervallo temperatura di funzionamento	-20 - 50 °C
Intervallo di temperatura	-40 - 70 °C
Range di umidità di funzionamento	10 - 95%
Umidità	10 - 95%
Dissipazione del calore	324,495 BTU/h

Dimensioni e peso	
Larghezza	440 mm
Profondità	270 mm
Altezza	43 mm
Peso	5,64 kg

Dati su imballaggio	
Larghezza imballo	508 mm
Profondità imballo	394 mm
Altezza imballo	90 mm
Peso dell'imballo	12,4 kg

Prestazione	
RAM installata	512 MB
Memoria flash	32 MB
Tempo medio tra guasti (MTBF)	562941 h

4718937636419

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 14-NOV-2026. Prints or copies of Information are only valid on the printed Publication date